

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A photographic film scanning system for scanning a film media containing at least one photographic image and for creating digital representations of the photographic image or images, the system comprising:

- a light source for projecting light through the film media;
- a light sensor for sensing the light projected through the film media and for generating pixel data;
- a film drive for advancing the film media between the light source and the light sensor;
- a lens located between the light source and the light sensor for directing the light projected through the film media onto the light sensor;
- a film type selection device adapted to manually select a type of film to be scanned;
- an adjustment device responsive to the film type selection device and adapted to automatically change the position of the lens and the position of the light sensor to provide proper focus for the selected type of film;
- and
- means for generating digital representations of the photographic images from the generated pixel data;
- and
- an infrared light filter located between the light source and the light sensor, the infrared light filter preventing infrared light from being projected on the light sensor.

2. (previously presented) The film scanning system of claim 1 wherein the film type selection device includes a first position and a

second position, the first position corresponding to 35mm film and the second position corresponding to APS film.

3. (previously presented) The film scanning system of claim 1 wherein the film type selection device includes a first position and a second position, the first position corresponding to 35mm film and the second position corresponding to 46mm film.

4. (previously presented) The film scanning system of claim 1, and further comprising a film color selection device adapted to manually select a film color.

5. (previously presented) The film scanning system of claim 4 wherein the film color selection device includes a first, a second and a third position, the first position corresponding to negative film, the second position corresponding to positive film and the third position corresponding to black and white film.

6. (previously presented) The film scanning system of claim 4, and further comprising a light filter responsive to the film color selection to move between the light source and the light sensor, the light filter reducing intensity of light incident on the light sensor when positioned between the light source and the light sensor.

7. (previously presented) The film scanning system of claim 1, and further comprising a gain adjustment device adapted to adjust a gain of the pixel data, and an offset adjustment device adapted to adjust an offset of the pixel data.

8. (previously presented) The film scanning system of claim 7 wherein the gain adjustment device and the offset adjustment device are programmable by user input.

9. (previously presented) The film scanning system of claim 1, and further comprising a speed adjustment device adapted to automatically adjust the speed of the film drive based on user entered scanning resolution data.

10. (original) The film scanning system of claim 1, and further comprising means for displaying the digital representations of the photographic images.

11. (original) The film scanning system of claim 1, and further comprising first and second position sensors, wherein the first position sensor detects when the lens reaches a first predetermined position, and the second position sensor detects when the light sensor reaches a second predetermined position.

12. (original) The film scanning system of claim 1, and further comprising means for bending the film media longitudinally as it passes between the light source and the light sensor.

13. (original) The film scanning system of claim 1, and further comprising a guide track consisting of a left guide to guide a first edge of the film media and a right guide to guide a second edge of the film media.

14. (previously presented) The film scanning system of claim 13, and further comprising a guide track adjustment device responsive to the film type selection device for adjusting the distance between the left guide and the right guide.

15. (canceled)

16. (currently amended) ~~The film scanning system of claim 1, and further comprising~~ A photographic film scanning system for scanning a film media containing at least one photographic image and for creating digital representations of the photographic image or images, the system comprising:

a light source for projecting light through the film media;

a light sensor for sensing the light projected through the film media and for generating pixel data;

a film drive for advancing the film media between the light source and the light sensor;

a lens located between the light source and the light sensor for directing the light projected through the film media onto the light sensor;

a film type selection device adapted to manually select a type of film to be scanned;

an adjustment device responsive to the film type selection device and adapted to automatically change the

position of the lens and the position of the light sensor
to provide proper focus for the selected type of film;
means for generating digital representations of the
photographic images from the generated pixel data;
and

a light tunnel located between the light source and the light sensor, the light tunnel preventing substantially all light from reaching the light sensor except the light projected through the film media.

17. (original) The film scanning system of claim 1, and further comprising a code sensor for projecting light through a first edge of the film media where coded data is located, the code sensor generating signals representative of the coded data on the film media.

18. (previously presented) A scanner for generating pixel data from photographic film media, the scanner comprising:

a first and a second inlet, the first inlet adapted to receive a plurality of types of photographic film strips, the second inlet adapted to receive slides;

film drive means for advancing the media through the scanner;

a first guide track coupled to the first inlet for guiding the film strips through the scanner;

a second guide track coupled to the second inlet for guiding the slides through the scanner;

a light source for projecting light through the film media;

a light sensor for sensing the light projected through the film media and for generating pixel data based upon the intensity of the light sensed; and

a lens located between the light source and the light sensor for directing the light projected through the film media onto the light sensor.

19. (original) The scanner of claim 18, and further comprising a film type selection means for manually selecting a type of film to be scanned.

20. (original) The scanner of claim 19 wherein the film type selection means includes a first position and a second position, the first position corresponding to 35mm film and the second position corresponding to APS film.

21. (original) The scanner of claim 19 wherein the film type selection means includes a first position and a second position, the first position corresponding to 35mm film and the second position corresponding to 46mm film.

22. (original) The scanner of claim 18, and further comprising film color selection means for manually selecting a film color.

23. (original) The scanner of claim 22 wherein the film color selection means includes a first, a second and a third position, the first position corresponding to negative film, the second position corresponding to positive film and the third position corresponding to black and white film.

24. (original) The scanner of claim 22, and further comprising a light filter responsive to the film color selection means to move between the light source and the light sensor, the light filter reducing intensity of light incident on the light sensor when positioned between the light source and the light sensor.

25. (original) The scanner of claim 18, and further comprising gain adjustment means for adjusting a gain of the pixel data, and offset adjustment means for adjusting an offset of the pixel data.

26. (original) The scanner of claim 25 wherein the gain adjustment means and the offset adjustment means are programmable by user input.

27. (original) The scanner of claim 18, and further comprising speed adjustment means for automatically adjusting the speed of the film drive means based on user entered scanning resolution data.

28. (original) The scanner of claim 18, and further comprising means for displaying the pixel data.

29. (original) The scanner of claim 19, and further comprising means responsive to the film type selection means for automatically

changing the position of the lens and the position of the light sensor to provide proper focus for the selected film type.

30. (original) The scanner of claim 29, and further comprising first and second position sensors, wherein the first position sensor detects when the lens reaches a first predetermined position, and the second position sensor detects when the light sensor reaches a second predetermined position.

31. (original) The scanner of claim 18, and further comprising means for bending the film media longitudinally as it passes between the light source and the light sensor.

32. (original) The scanner of claim 19 wherein the first guide track comprises a left guide to guide a first edge of a film strip and a right guide to guide a second edge of a film strip, and the scanner further comprises guide track adjustment means responsive to the film type selection means for adjusting the distance between the left guide and the right guide.

33. (original) The scanner of claim 18, and further comprising an infrared light filter located between the light source and the light sensor, the infrared light filter for preventing infrared light from being projected on the light sensor.

34. (original) The scanner of claim 18, and further comprising a light tunnel located between the light source and the light sensor, the light tunnel preventing substantially all light from reaching the light sensor except the light projected through the film media.

35. (original) The scanner of claim 18, and further comprising a code sensor for projecting light through a first edge of the film media where coded data is located, the code sensor generating signals representative of the coded data on the film media.

Claims 36 - 38 have been cancelled.

39. (canceled)